

## INDUSTRIAL FLY SCREEN DOOR

A 46mm powder coated aluminium framed door. 195mm wide mid push plate and kick plate fitted to the bottom of the door to add the strength and durability. Stainless steel mesh is held in place with a pliable rubber gasket designed to keep the mesh taught and secure. A stainless steel perforated plate option available.



### **How they work**

A one way swing door designed to work in front of, or behind the exterior door and hinged to the existing framework.

Every door comes complete with its own self closer.

### **Suitability**

This door can be fitted to UPVC, timber and metal casings, which makes it ideal for domestic or commercial use with light traffic.

### **Removal**

Door and closer can be removed easily without the use of specialized tools.

### **Maintenance**

The door closer is maintenance free.

To keep door hinges working effectively, spray WD40 or a little light machine oil into the moving parts periodically. The powder coating can be cleaned with a cream cleaner to restore its original condition.

All meshes can be cleaned with warm, soapy water to remove grease or dirt.

Stainless Steel mesh can be power washed if desired.

Dusty screens should be vacuumed or brushed clean.

### **Technical**

Standard colours – White and brown

Fibre Mesh – 18 x 16 weave, grey

Stainless Steel – 16 x 16 weave, Natural. Perforated Sheet 1.2mm holes

### **Guarantee**

12 months on all workmanship under normal wear and tear.